LAGO.BG



PREMIUM ELECTRIC OUTBOARD MOTORS

HASWING TROLLING MOTORS









MODEL: 产品型号:

50701 / 50702 / 50703

Power of thrust: 峰值推力:

30Lbs / 40Lbs / 55Lbs

Max Voltage: 电压:

DC 12V (AII)

Power - Max: 功率: 360W / 500W / 600W

Amp - Max: 电流: 30A / 42A / 50A

Depth Adjustment: 深度调节:

Depth Collar (All)

Prop Type: 螺旋桨型号:

2-blade prop 9 inch diam (50701,50702) 3-blade prop 9.3 inch diam (50703)

Prop Speed at Full Power: 转速: Max. 1200 / 1380 / 1250 rpm underwater

Battery Type Required: 电池要求:

1 x 105AH deep cycle (All)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

≤50db (AII)

Weight (N.W.): 重量: 6.6kg / 7.1 kg / 8.6kg

Shaft Type: 主杆类型:

Cast Aluminum (All)

Shaft Length: 主杆长度: 800mm / 900mm

Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

4m / 4.7m / 5.5m



LEVEL LOCK BRACKET 角度调节支架

Offers 10 tilt position.



FOLDABLE HANDLE 手柄角度调节

Angle of tiller handle can adjust from 0 to 110 degrees.



SPEED CONTROL 推进变速调节

Features 5-speed levels of forward and 3-speed levels of reverse control.



EXTENDABLE HANDLE 伸缩性操纵手柄

350mm length of handle extension.



BATTERY METER

Display 5 levels of battery power.

The Osapian range features durable 12 volt motors and available in 30, 40 and 55Lbs models. Osapian motors are equipped with 5 forward and 3 reverse positions. Osapian models are light-weight (from 6.6kg), easily portable and very compact thanks to their collapsible tiller handle.

Depth height can easily be adjusted so you can motor in virtually any depth of water. The steering lever adjusts to different angles, is telescopic and extendable for comfortable control. All Osapian models features an LED battery level indicator. Suitable for both salt and fresh water use.



MODEL: 产品型号:

50708 / 50714 / 50716

Power of thrust: 峰值推力:

30Lbs / 40Lbs / 55Lbs

Max Voltage: 电压:

DC 12V (AII)

Power - Max: 功率: 360W / 500W / 600W

Amp - Max: 电流: 30A / 42A / 50A

Depth Adjustment: 深度调节:

Depth Collar (All)

Prop Type: 螺旋桨型号:

2 blade prop 9inch diam (50708,50714) 3 blade prop 9.3inch diam (50716)

Prop Speed at Full Power: 转速: Max. 1200 / 1380 / 1250 rpm underwater

Battery Type Required: 电池要求: 1x105AH deep cycle (All)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

≤50db (AII)

Weight (N.W.): 重量: 6.3kg / 6.9 kg / 8.4kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度: 800mm / 900mm / 900mm

Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

4m / 4.7m / 5.5m



LEVEL LOCK BRACKET 角度调节支架

Offer 10 levels of tilting position.



SPEED CONTROL 推进变速调节

Provide 5-speed levels of forward and 3-speed levels of reverse control.



EXTENDABLE HANDLE 伸缩性操纵手柄

350mm length of handle extension.



BATTERY METER 由源显示

Display 3 levels of battery power.

The Osapian F range features durable 12 volt motors and available in 30, 40 and 55lbs models. Osapian F motors are equipped with 5 forward and 3 reverse positions. Osapian F models are light- weight (from 6.3kg).

The depth height can easily be adjusted, so you can motor in virtually any water.

The steering lever adjusts to different angles, is telescopic and extendable for comfortable control. The Osapian F models also features an LED battery level indicator. Suitable for both salt and fresh water.





MODEL: 产品型号:

50717

Power of thrust: 峰值推力:

55Lbs

Max Voltage: 电压:

DC 12V

Power - Max: 功率:

660W

Amp - Max: 电流:

50A

Depth Adjustment: 深度调节:

Electric Trim System

Prop Type: 螺旋桨型号: 3 blade prop / 9.3inch diam

Prop Speed at Full Power: 转速:

Max.1250 rpm underwater

Battery Type Required: 电池要求:

1 x105AH Deep Cycle

Steering: 转向操控: 90 degree control

Decibel Level (db): 噪音等级:

≤50db

Weight (N.W.): 重量:

14.5kg

Shaft Type: 主杆类型:

Stainless steel


Shaft Length: 主杆长度:

and fresh water use.

Variable

Max Boat Length (Suggestion): 船长

5.5m



ELECTRIC LIFTING 电动升降调节

Press to control the motor up or down. 265mm depth of motor extension.



2:1 STEERING 2:1 操控转向手柄

90 degree -2:1 steering system to control the motor 180 degree turning.



Level Lock Bracket 角度调节支架

Offers 10 levels of tilting position.



FOLDABLE HANDLE 角度调节手柄

Trolling handle has folding functions. Folding angle:120°



BATTERY METER 电源显示

Displays 3 levels of battery power.

The Comax N electric trolling motor is specifically designed for electric only waterways featuring a durable 12 volt 55 lbs thrust motor and innovative integrated electric trim system, 2:1 steering system to aid maneuvering in tighe spaces and a telescopic tiller handle. Comax N motors are equipped with a step-less digital speed controller which provides precise power control, ideal for trolling at the optimum speed. The Comax N also features an LED battery level indicator. Suitable for both salt















MODEL: 产品型号:

50735

Power of thrust: 峰值推力:

20Lbs

Max Voltage: 电压:

DC 12V

Power - Max: 功率:

200W

Amp - Max: 电流:

17A

Depth Adjustment: 深度调节:

Depth Collar

Prop Type: 螺旋桨型号: 2 blade prop / 5.9inch diam

Prop Speed at Full Power: 转速:

Max.1200 rpm underwater

Battery Type Required: 电池要求:

1x20AH Deep Cycle **Steering:** 转向操控: 360 degree control

Decibel Level (db): 噪音等级:

≤50db

Weight (N.W.): 重量:

2.3kg

Shaft Type: 主杆类型:

Cast Aluminium

Shaft Length: 主杆长度:

600mm

Colour: 颜色:

Black

Max Boat Length (Suggestion): 船长:

3m



FOLDABLE HANDLE 手柄角度调节

Angle of the handle can adjust 0 to 110 degrees.



BATTERY METER 电源显示

Display 3 levels of battery power.



SPEED CONTROL 推进变速调节

Provide Forward / Reverse with High and Low speed control.



LEVEL LOCK BRACKET 角度调节支架

Offer 0 degree and 90 degree of tilting position.

The W20 features a durable 12 volt motor offering 20lbs of thrust. W20 features 2 forward and 2 reverse speeds. At just 2.3kgs it is very light, easily portable and very compact thanks to its collapsible tiller handle.

Depth height is easily adjustable, so you can motor in virtually any depth of water. The tiller handle adjusts to different angles making it easy to stow and the motor also features an LED battery level indicator. Suitable for both salt and fresh water use.





MODEL: 产品型号: 50700 / 50718D

Power of thrust: 峰值推力:

55Lbs / 80Lbs

Max Voltage: 电压:

DC 12V / 24V

Power - Max: 功率: 600W / 1080W

Amp - Max: 电流:

50A / 45A

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号:

3-blade prop / 9.3 inch diam (50700) 2-blade prop / 11.4 inch diam (50718D)

Prop Speed at Full Power: 转速: Max. 1250 rpm underwater (50700) Max. 1500 rpm underwater (50718D)

Battery Type Required: 电池要求:

1 x 105AH Deep Cycle (50700) 2 x 105AH Deep Cycle (50718D)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

50db (All)

Weight (N.W.): 重量:
13.7kg / 17.5kg / 19.2kg
Shaft Type: 主杆类型:
Cast Aluminium (All)
Shaft Length: 主杆长度:
1200mm / 1370mm / 1490mm

Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

5.5m / 6.5m



Deploy/Stow pedal 推进器收放踏板

Press it to deploy or stow the motor easily.



REMOTE CONTROLLER 工线運換器

Function: On/Off, Speed Up/Down, Full Speed, Turn Left/Right, Pairing.



WIRED FOOT CONTROLLER 线控脚踏控制器 (选配)

LCD Display; Function: On/Off, Speed Up/Down, Full Speed, Turn Left/Right.



INDIVIDUAL FIN 独立鳍翼设计

The individual fin will protect motor and propeller from being hit under water.



BATTERY METER 电源显示

Display 3 levels of battery power.

The Cayman B Bow Mount Trolling Motor was developed for serious fishermen requiring the versatility of controlling their motor via a wireless hand remote or wired foot control pedal. This feature-packed bow mount trolling motor comes standard with a wireless hand control, sacrificial anode and encapsulated electronics. Supplied standard with all the necessary stainless steel nuts and bolts to fit straight onto the boat, or option up with our Quick Release Bracket with a foot print of just 120mm x 200mm when not in use. All models feature LED battery meters. Optional wired foot controller and quick release mounting plate are a perfect partner for your Cayman B motor. Suitable for both salt and fresh water use.

MODEL: CAYMAN B/with GPS





4 Advanced Functions



Actual model may vary from image!

Record Route



Anchor







SPECIFICATIONS

MODEL: 产品型号: 50736 / 50737

Power of thrust: 峰值推力:

55Lbs / 80Lbs

Max Voltage: 电压:

DC 12V / 24V

Power - Max: 功率:

600W / 1080W

Amp - Max: 电流:

50A / 45A

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号:

3blade prop / 9.3inch diam (50736) 2blade prop / 11.4inch diam (50737)

Prop Speed at Full Power: 转速:

Max. 1250 rpm underwater (50736) Max. 1500 rpm underwater (50737)

Battery Type Required: 电池要求:

1 x105AH Deep Cycle (50736) 2 x105AH Deep Cycle (50737)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

50db (All)

Weight (N.W.): 重量:

13.9kg / 15.1kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度:

1200mm / 1370mm / 1520mm / 1830mm

Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

5.5m / 6.5m



GPS SMART NAVIGATION SYSTEM GPS智能导航系统

- Record Routes
- 2. GPS Navigation
- 3. Anchor
- 4. Cruise Control



SMART PHONE OPERATING SYSTEM 智能手机终端控制

Download the Helmsman APP to operate all functions with your smart phone-Android or IOS.



BATTERY METER

Displays 3 levels of battery power status.



DEPLOY/STOW PEDAL 推进器收放踏板

Press it to deploy or stow the motor easily.



REMOTE CONTROLLER

Function: On/Off. Speed Up/Down, Full Speed, Turn Left/Right, Pairing.

The Cayman B/with GPS Bow Mount Trolling Motors are renowned for their spot lock accuracy, robustness and durability. Used by serious fishermen who require the versatility of quiding their motor via a wireless hand remote or wireless foot remote pedal. Spot lock (anchor mode) is accessible on the remote, as well as Helmsman APP. Very accurate spot lock holds your boat where it should be, Right on the fish. A feature-packed bow mount trolling motor comes standard with a wireless hand control, sacrificial anode. Encapsulated electronics and all the necessary 316 stainless steel nuts and bolts to fit straight onto the boat, or option up with our quick release plate with a foot print of just 120mm x200mm when not in use. Helmsman GPS smart navigation system and smart phone operation (including Apple Smart Watch) system is free to download. All models feature LED battery status lights. Optional wireless foot controller and guick release mounting plate are available. Suitable for both salt and fresh water.



型号 Model	杆长 Shaft Length	有效深度 Effective Depth
	1520mm	1320mm
50739	1830mm	1630mm
50738	2100mm	1900mm
	2500mm	2300mm

牺牲阳极 Sacrificial Anode

Wireless Foot Controller

DD Brush Motor

无线脚踏遥控器

图片与实物略有不同! 有刷直驱电机

with

50738

Actual model may vary from image!



with

50739

4 Advanced Functions











独立鳍

Individual Fin

SPECIFICATIONS

MODEL: 产品型号: 50739 / 50738

Power of thrust: 峰值推力:

80Lbs / 120Lbs

Max Voltage: 电压:

DC 24V / 36V

Power - Max: 功率: 1080W / 1620W

Amp - Max: 电流:

45A (AII)

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号:

2blade prop / 11.4inch diam (All)

Prop Speed at Full Power: 转谏: Max. 1500 rpm underwater (All)

Battery Type Required: 电池要求:

2 x105AH Deep Cycle (50739) 3 x105AH Deep Cycle (50738)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

50db (All)

Weight (N.W.): 重量:

21kg / 22.7kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度:

1520mm / 1830mm / 2100mm / 2500mm

Colour: 颜色: Black (AII)

Max Boat Length (Suggestion): 船长:

6.5m / 7m



GPS智能导航系统

- 1. Record Routes
- 2. GPS Navigation

GPS SMART NAVIGATION SYSTEM

- 3. Anchor
- 4. Cruise Control



MART PHONE OPERATING SYSTEM 智能手机终端控制

Download the Helmsman APP to operate all functions with your smart phone-Android or IOS.



BATTERY METER 电源显示

Displays 3 levels of battery power status.



DEPLOY/STOW PEDAL 推进器收放踏板

Press it to deploy or stow the motor easily.



REMOTE CONTROLLER

Function: On/Off,



Speed Up/Down, Full Speed, Turn Left/Right, Pairing.

The Cayman B/with GPS Bow Mount Trolling Motor aimed at serious fishermen who require the versatility of guiding their motor via a wireless hand remote or wireless foot remote pedal. This feature packed bow mount trolling motor comes standard with a wireless hand control, sacrificial anode and encapsulated electronics. Supplied standard with all the necessary stainless steel nuts and bolts to fit straight onto the boat, or option up with our quick release plate with a foot print of just 120mmx200mm when not in use. GPS smart navigation system and smart phone operation system are available for all motors. All motors feature LED battery meters. Upgraded packages are available which include the wireless foot remote controller and quick release mounting plate. Suitable for both salt and fresh water.



MODEL: 产品型号: 50706 / 50757

Power of thrust: 峰值推力:

55Lbs / 80Lbs

Max Voltage: 电压:

DC 12V / 24V

Power - Max: 功率: 600W / 1080W

Amp - Max: 电流:

50A / 45A

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号:

3blade prop / 9.3inch diam (50706) 2blade prop / 11.4inch diam (50757)

Prop Speed at Full Power: 转速:

Max. 1250 rpm underwater (50706) Max. 1500 rpm underwater (50757)

Battery Type Required: 电池要求:

1 x105AH Deep Cycle (50706) 2 x105AH Deep Cycle (50757)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

50db (AII)

Weight (N.W.): 重量:

11.8kg / 13.0kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度:

1000mm (All) **Colour:** 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

5.5m / 6.5m



LEVEL LOCK BRACKET 角度调节支架

Offer 0°~85° of tilting position.



REMOTE CONTROLLER 无线谣控器

Function: On/Off, Speed Up/Down, Full Speed, Turn Left/Right, Pairing.



ional! WIRED FOOT CONTROLLER 线控脚踏控制器 (选配)

LCD Display; Function: On/Off, Speed Up/Down, Full Speed, Turn Left/Right.



INDIVIDUAL FIN 独立鳍翼设计

The individual fin will protect motor and propeller from being hit under water.



BATTERY METER 由源显示

Display 3 levels of battery power.

The Cayman T transom Mount Trolling Motor aimed at serious fishermen who require the versatility of guiding their motor via a wireless hand remote or wired foot control pedal. This feature packed transom mount trolling motor comes standard with a wireless hand control, sacrificial anode and encapsulated electronics. Cayman T motors are equipptd with one-way stepless speed control. The depth height can easily be adjusted, so you can motor in virtually any water. All motors feature LED battery meters. Upgraded packages are available which include the wired foot controller. Suitable for both salt and fresh water.



Actual model may vary from image!







SPECIFICATIONS

MODEL: 产品型号: 50711 / 50712 Shaft Power: 动力:

1HP / 2HP

Comparable petrol outboards (thrust):

等效汽油机: 2HP/3HP

Power of thrust: 峰值推力:

65Lbs / 85Lbs Max Voltage: 电压: DC 12V / 24V

Power - Max: 功率: 600W / 960W

Amp - Max: 电流:

50A / 40A

Depth Adjustment: 深度调节:

Depth Collar (All) Prop Type: 螺旋桨型号:

3 blade prop 9.3inch diam (All) Prop Speed at Full Power: 转速:

Max. 1250 rpm underwater(50711) Max. 1350 rpm underwater(50712)

Battery Type Required: 电池要求:

1x105AH deep cycle (50711)

2x105AH deep cycle (50712) Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

≤55db (AII)

Weight (N.W.): 重量:

6.7kg / 7.1 kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度:

900mm(All) Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

6m / 6.5m



LEVEL LOCK BRACKET 角度调节支架

Offer 10 levels of tilting position.



SPEED CONTROL 推进变速调节

Provide 5-speed levels of forward and 3-speed levels of reverse control.



BATTERY METER 电源显示

Display 3 levels of battery power.

These Protruar models are equipped with innovative and powerful 12V or 24V motors, providing excellent propulsion for a wide range of boats and waterways. motors are equipped with 5 forward and 3 reverse positions.

Depth height can easily be adjusted so you can motor in virtually any depth of water. The steering lever adjusts to different angles, is telescopic and extendable for comfortable control. All models features an LED battery level indicator. Suitable for both salt and fresh water use.





MODEL: 产品型号: 50728 / 50713 Shaft Power: 动力:

3HP / 4HP

Comparable petrol outboards (thrust): 等效汽油机:

4HP / 5HP

Peak Thrust in Lbs: 峰值推力:

110Lbs / 130Lbs

Max Voltage: 电压:

DC 24V (AII)

Power - Max: 功率: 1200W / 1800W

Amp - Max: 电流:

50A / 75A

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号:

3blade prop / 11.8inch diam (All)

Prop Speed at Full Power: 转速: Max. 630 rpm underwater (50728)

Max. 1100 rpm underwater (50713)

Battery Type Required: 电池要求:

2x105AH Deep Cycle (50728) 2x120AH Deep Cycle (50713)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

65db (AII)

Weight (N.W.): 重量:

8.0kg / 8.3kg

Shaft Type: 主杆类型:

Cast Aluminium / Stainless Steel

Shaft Length: 主杆长度: 900mm / 1000mm

Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

7m / 7.5m



FOLDABLE HANDLE 操控杆角度调节

This Trolling handle has the folding functions. Folding angle: 100°



EVEL LOCK BRACKET 角度调节支架

Offer 7 levels of tilting position.



SPEED CONTROL 无级变速调节+熄火钥

Digital technology provide stepless forward and reverse speed control.



BATTERY METER

Display 5 levels of battery power.



PROP-CLUTCH 螺旋桨离合功能

Prop temporarily disengages on hard impact preventing damage to prop motor.

The Protruar G series are equipped with powerful 24V brushless motors and provide excellent propulsion for a wide range of boats and waterways. Equipped with step-less adjustable speed control and a safety lanyard. The motor can easily be tilted in and out of the water and the trim height is adjustable by way of a guick lock mechanism, so you can motor in almost any level of water. As an added safety feature, the Protruar G series is equipped with anti-impact propeller technology, meaning that in the event of impact it will temporarily disengage to protect the motor and the propeller. They features an LED battery level indicator. Suitable for both salt and fresh water use.



MODEL: 产品型号: 50744 / 50745 /50715

Shaft Power: 动力: 1HP / 2HP / 3HP

Comparable petrol outboards (thrust):

等效汽油机: 2HP/3HP/4HP

Peak Thrust in Lbs: 峰值推力:

65Lbs / 85Lbs / 110Lbs Max Voltage: 电压: DC 12V / 24V / 24V Power - Max: 功率: 600W / 960W /1440W Amp - Max: 电流: 50A / 40A / 60A

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号: 3blade prop / 9.3inch diam (All) Prop Speed at Full Power: 转速: Max. 1250 rpm underwater (50744) Max. 1350 rpm underwater (50745)

Max. 1450 rpm underwater (50715) **Battery Type Required:** 电池要求:

1x105AH Deep Cycle (50744) 2x105AH Deep Cycle (50745,50715)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

<55db (AII)

Weight (N.W.): 重量: 6.6kg / 6.9kg / 9.9kg Shaft Type: 主杆类型:

Cast Aluminium (50744,50745) Stainless Steel (50715)

Shaft Length: 主杆长度:

900mm (All) **Colour:** 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

6m / 6.5m / 7m



LEVEL LOCK BRACKET 角度调节支架

Offer 10 or 7 levels of tilting position.



SPEED CONTROL 推进变速调节

Digital technology provide stepless forward and reverse speed control.



EXTEND & FOLD 伸缩+角度调节操纵手柄

400mm length of handle extension. Trolling handle has folding functions. Folding angle:180°



BATTERY METER 电源显示

Display 3 levels of battery power.

These Protruar models are equipped with innovative and powerful 12V or 24V motors, providing excellent propulsion for a wide range of boats and waterways. Equipped with step-less adjustable speed control. The motor can easily be tilted in and out of the water and the trim height is adjustable by way of a quick lock system, so you can motor in almost any level of water. They feature an LED battery level indicator and are suitable for both salt and fresh water use.





MODEL: 产品型号:

50719

Shaft Power: 动力:

5HP

Comparable petrol outboards (thrust):

等效汽油机:

6HP

Peak Thrust in Lbs: 峰值推力:

160Lbs

Max Voltage: 电压:

DC 24V

Power - Max: 功率:

2520W

Amp - Max: 电流:

105A

Depth Adjustment: 深度调节:

Depth collar

Prop Type: 螺旋桨型号: 3blade prop / 10.7inch diam

Prop Speed at Full Power: 转速:

Max. 1450 rpm underwater

Battery Type Required: 电池要求:

2x120AH Deep Cycle Steering: 转向操控: 360 degree control

Decibel Level (db): 噪音等级:

≤55db

Weight (N.W.): 重量:

14kg

Shaft Type: 主杆类型:

Stainless Steel

Shaft Length: 主杆长度:

1000mm Colour: 颜色:

Black



SPEED CONTROL 推进变速调节

Digital technology provide stepless forward and reverse speed control. With magnetic kill switch.



LEVEL LOCK BRACKET 角度调节支架

Offer 7 levels of tilting position.



EXTEND & FOLD 伸缩+角度调节操纵手柄

400mm length of handle extension. Trolling handle has folding functions. Folding angle: 180°



BATTERY METER 电源显示

Display 3 levels of battery power.

Max Boat Length (Suggestion): 船长:

The Protruar 5.0 is equipped with a powerful 24V brushless motor offering a massive 160 lbs thrust, offering excellent propulsion for a wide range of boats and waterways. Equipped with step-less adjustable speed control and a magnetic safety lanyard. The motor can easily be tilted in and out of the water and the trim height is adjustable by way of a quick lock mechanism, so you can motor in almost any level of water. This Protruar model also features an LED battery level indicator. Suitable for both salt and fresh water use.



MODEL: 产品型号: 50754 / 50756

Shaft Power: 动力:

2HP/3HP

Comparable petrol outboards (thrust):

等效汽油机: 3HP/4HP

Peak Thrust in Lbs: 峰值推力:

85Lbs/110Lbs

Max Voltage: 电压:

DC 12V (AII)

Power - Max: 功率:

720W/900W

Amp - Max: 电流:

60A/75A

Depth Adjustment: 深度调节:

Depth collar (All)

Prop Type: 螺旋桨型号:

3blade prop / 10.7inch diam (All)

Prop Speed at Full Power: 转速:

Max. 1150 rpm underwater (50754) Max. 1250 rpm underwater (50756)

Battery Type Required: 电池要求:

1x120AH Deep Cycle (All) Steering: 转向操控:

360 degree control (All)

Decibel Level (db): 噪音等级:

55db (All)

Weight (N.W.): 重量:

10.3kg/14.5kg

Shaft Type: 主杆类型:

Stainless Steel (All)

Shaft Length: 主杆长度:

900mm/1000mm Colour: 颜色: Black (All)

Max Boat Length (Suggestion): 船长:



SPEED CONTROL 推进变速调节

PWM controller provide stepless forward and reverse speed control. With magnetic kill switch.



LEVEL LOCK BRACKET 角度调节支架

Offers 7 levels of tilting position.



EXTEND & FOLD 伸缩+角度调节操纵手柄

400mm length of handle extension. Trolling handle has folding functions. Folding angle: 180°



BATTERY METER 电源显示

Displays 3 levels of battery power status.

6.5m/7m

The Protruar 3.0 is equipped with an innovative and powerful 110 lbs thrust from a 12V brushless motor, providing excellent propulsion for a wide range of boats and waterways. Equipped with step-less adjustable speed control and a magnetic safety lanyard. This motor can easily be tilted in and out of the water and the trim height is adjustable by way of a guick lock mechanism, so you can motor in almost any level water. It features an LED battery level indicator, and is suitable for both salt and fresh water use.



图片与实物略有不同! Actual model may vary from image!





MODEL: 产品型号:

50765

Shaft Power: 动力: 55Lbs/40Lbs/30Lbs

Comparable petrol outboards (thrust):

等效汽油机:

1.5HP/1.2HP/1HP

Peak Thrust in Lbs: 峰值推力:

55Lbs/40Lbs/30Lbs Max Voltage: 电压:

DC 12V

Power - Max: 功率: 660W/500W/360W **Amp - Max:** 电流: 55A/42A/30A

Depth Adjustment: 深度调节:

Depth collar

Prop Type: 螺旋桨型号: 2blade prop /7.6inch diam

Prop Speed at Full Power: 转速:

Max. 1600 rpm underwater

Battery Type Required: 电池要求:

1x105AH Deep Cycle **Steering:** 转向操控: 360 degree control

Decibel Level (db): 噪音等级:

≤50db

Weight (N.W.): 重量:

4.4kg

Shaft Type: 主杆类型:

Cast Aluminium

Shaft Length: 主杆长度:

800mm

Colour: 颜色:

Black

Max Boat Length (Suggestion): 船长:

5.5m



LEVEL LOCK BRACKET 角度调节支架

Offer 10 or 7 levels of tilting position.



SPEED CONTROL 推进变速调节

PWM controller provide stepless forward and reverse speed control.



EXTEND & FOLD 伸缩+角度调节操纵手柄

400mm length of handle extension. Trolling handle has folding functions. Folding angle:180°



BATTERY METER 中海自二

Display 3 levels of battery power.



Exchanged Button 换挡按键

With three-gear switching function. (30、40、50Lbs)

The Protruar Genius 55 lbs range features durable 12 volt broushless motors featuring selectable lbs thrust of 30, 40 or 55 models. Want to extend run-times, then select the lower lbs thrust mode.

Motor depth can easily be adjusted so you can motor in virtually any depth of water. The steering lever adjusts to different angles, is telescopic and extendable for comfortable control. All Protruar Genius models features an LED battery level indicator. Suitable for both salt and fresh water use.

MODEL: ULTIMA

With LIPO Battery 29.6V-3.0HP

电动无刷推进器带可充电理电池豪华系列



无级变速可伸缩手柄 Stepless Speed Control Extendable Handle



(59925)

29.6V-30Ah

包含可充电锂电池

Rechargeable LIPO Battery

Included

7.8kg





DD Brushless Motor

无刷直驱电机







紧急停止开关

Magnetic Kill Switch

Included

牺牲阳极

Sacrificial Anode

图片与实物略有不同

Output: 4A Charger Included Input:100V-240V 充电器已配备





SPECIFICATIONS

MODEL: 产品型号:

50741

Shaft Power: 动力:

3HP / 1HP

Comparable petrol outboards (thrust):

等效汽油机: 4HP / 2HP

Peak Thrust in Lbs: 峰值推力:

110Lbs / 65Lbs

Max Voltage: 电压:

DC 29.6V

Power - Max: 功率: 1030W / 480W

Amp - Max: 电流:

35A / 16A

Depth Adjustment: 深度调节:

Not Available

Prop Type: 螺旋桨型号: 3blade prop / 9.3inch diam

Prop Speed at Full Power: 转速:

Max. 1530 rpm underwater

Battery Type Required: 电池要求: 29.6V, 30AH rechargeable LIPO battery

Charging Time: 充电时间:

8-9 hours

Steering: 转向操控: 360 degree control

Decibel Level (db): 噪音等级:

≤55db

Weight (N.W.): 重量:

15.9kg

Shaft Type: 主杆类型:

Cast Aluminium

Shaft Length: 主杆长度: 540/630/700/760mm

Colour: 颜色:

Black

Max Boat Length (Suggestion): 船长:



SPEED CONTROL

PWM controller provide stepless forward and reverse speed control. With magnetic kill switch.



EXTEND & FOLD 伸缩+角度调节操纵手柄

400mm length of handle extension. Trolling handle has folding functions. Folding angle: 180°



LEVEL LOCK BRACKET 角度调节支架

Offer 7 levels of tilting position.



BATTERY METER 电源显示

Display 5 levels of battery power.



Exchanged Button 换挡按键

With high and low gear switching function. (1HP, 3HP)

The Ultima 3.0 provides 110 lbs of thrust from a 29.6V LIPO(lithium polymer) battery powering a brushless motor. An excellent motor for small craft such as tender, inflatable,car toppers and Haswing Portable Assembly Boat, Equipped with step-less adjustable speed control and a magnetic safety lanyard. The motor can easily be tilted in and out of the water so you can motor in almost any level of water. The LIPO battery is removable for charging and a spare battery option is available.Battery charger provided.LED battery level indicator provides battery status at a glance. Suitable for both salt and fresh water use.





MODEL: VENTURA T



电动元刷推进器豪华系列









SPECIFICATIONS

MODEL: 产品型号:

50749

Shaft Power: 动力:

5HP

Comparable petrol outboards (thrust):

等效汽油机:

6HP

Peak Thrust in Lbs: 峰值推力:

160Lbs

Max Voltage: 电压:

DC 24V

Power - Max: 功率:

2520W

Amp - Max: 电流:

105A

Depth Adjustment: 深度调节:

Not Available

Prop Type: 螺旋桨型号: 3blade prop / 10.7inch diam

Prop Speed at Full Power: 转速:

Max. 1450 rpm underwater

Battery Type Required: 电池要求:

2x120AH Deep Cycle Steering: 转向操控: 360 degree control

Decibel Level (db): 噪音等级:

≤55db

Weight (N.W.): 重量:

15.7kg

Shaft Type: 主杆类型: Stainless Steel + Aluminium

Shaft Length: 主杆长度:

760/630mm

Colour: 颜色:

Black

Max Boat Length (Suggestion): 船长:



SPEED CONTROL 推进变速调节

PWM controller provide stepless forward and reverse speed control. With magnetic kill switch



LEVEL LOCK BRACKET 角度调节支架

Offer 7 levels of tilting position.



EXTEND & FOLD

400mm length of handle extension. Trolling handle has folding functions. Folding angle: 180°



BATTERY METER LED电源电压显示

Shows voltage of battery all the time.

The Ventura T is equipped with a brushless 5.0/24V motor and is excellent for the propulsion of a wide range of boats and waterways. This powerful motor is equipped with step-less adjustable speed control and a safety lanyard. The motor can easily be tilted in and out of the water, so you can motor in virtually any water. The Ventura T model also features an LED battery level indicator. Suitable for both salt and fresh water.

MODEL: VENTURA F



支架

Level Lock Bracket

ncluded

前进/后退无级调速

Stepless Speed F/R

电量指示区

Battery Meter

760mm

杆长可定制

Short & long

shaft lengths

available

牺牲阳极 Sacrificial Anode

电动元刷推进器豪华方向盘系列 Steering Wheel Series



需要另配方向盘! Steering Wheel Unit Is Required!



紧急停止开关 Magnetic Kill Switch Included

DD Brushless Motor 无刷直驱电机

图片与实物略有不同! Actual model may vary from image!







SPECIFICATIONS

MODEL: 产品型号:

50752

Shaft Power: 动力:

5HP

Comparable petrol outboards (thrust): 역效海流油机

等效汽油机:

6HP

Peak Thrust in Lbs: 峰值推力:

160Lbs

Max Voltage: 电压:

DC 24V

Power - Max: 功率:

2520W

Amp - Max: 电流:

105A

Depth Adjustment: 深度调节:

Not Available

Prop Type: 螺旋桨型号: 3blade prop / 10.7inch diam

Prop Speed at Full Power: 转速:

Max. 1450 rpm underwater

Battery Type Required: 电池要求:

2x120AH Deep Cycle **Steering:** 转向操控: 360 degree control

Decibel Level (db): 噪音等级:

≤55db

Weight (N.W.): 重量:

15.7kg

Shaft Type: 主杆类型: Stainless Steel + Aluminium

Shaft Length: 主杆长度:

760/630mm **Colour:** 颜色:

Black

Max Boat Length (Suggestion): 船长:

8m



STEPLESS SPEED CONTROLLER 无级变速器及感应开关

Digital technology provide stepless forward and reverse speed control. With magnetic kill switch is included.



LEVEL LOCK BRACKET 角度调节支架

Offer 4 levels of tilting position with 3 angles additional option.



STEERING WHEEL CONTROL 另购方向盘操控

An additional steering wheel unit is required. The steering angle: from -45° to +45°.



BATTERY METER LED电源电压显示

Shows voltage of battery all the time.

The Ventura F series are equipped with a powerful 24V brushless motor offering up to 160 lbs thrust and are excellent for the propulsion of a wide range of boats and waterways. These powerful motor are equipped with step-less adjustable speed control and a magnetic safety lanyard. The motor can easily be tilted in and out of the water, so you can motor in almost any level of water. The Ventura F series features digital LED battery level indicator. An additional steering wheel unit is required. Suitable for both salt and fresh water use.



图片与实物略有不同! Actual model may vary from image!







SPECIFICATIONS

MODEL: 产品型号: 50731 / 50732 Shaft Power: 动力: 8HP / 10HP

Comparable petrol outboards (thrust): 等效汽油机:

10HP / 12HP

Peak Thrust in Lbs: 峰值推力: 250Lbs / 300Lbs

Max Voltage: 电压: DC 48V (All)

Power - Max: 功率: 4320W / 6000W **Amp - Max:** 电流:

90A / 125A **Depth Adjustment:** 深度调节:

Not Available (All)

Prop Type: 螺旋桨型号: 3blade prop / 11.8inch diam (All)

Prop Speed at Full Power: 转速: Max. 1050 rpm underwater (50731) Max. 1200 rpm underwater (50732)

Battery Type Required: 电池要求:

4x120AH Deep Cycle (50731) 4x250AH Deep Cycle (50732)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

75db (All)

Weight (N.W.): 重量:

27.3kg / 28.8kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度:

540/670mm (All) **Colour:** 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

9m (All)



SPEED CONTROL 推进变速调节

PWM controller provide stepless forward and reverse speed control. With magnetic kill switch.



EXTEND & FOLD 伸缩+角度调节操纵手柄

360mm length of handle extension. Trolling handle has folding functions. Folding angle:180°



LEVEL LOCK BRACKET 角度调节支架

Offer 3 levels of tilting position, the angle is 18, 27, 60 degree.



BATTERY METER LED电源电压显示

Shows voltage of battery all the time.



WATER COOLING 循环式水冷系统

Water cooling system is available when the motor is working forward.

The Armada T series are equipped with efficient 48V brushless motors providing powerful propulsion for a wide range of boats operating in various waterways. They offer flexible step-less speed adjustment and a safety lanyard offer an added degree of safty. These motors can easily be tilted in and out of the water so you can motor in almost any water level. The Armada T models also feature a digital LED battery level indicator. Suitable for both salt and fresh water use.

MODEL: ARMADA F





电动元则推进器豪华方向盘系列 Stooring Wheel Series

Steering Wheel Series



无刷齿轮箱变速电机



需要另配方向盘! Steering Wheel Unit Is Required!





图片与实物略有不同! Actual model may vary from image!







SPECIFICATIONS

MODEL: 产品型号: 50733 / 50734 Shaft Power: 动力: 8HP / 10HP

Comparable petrol outboards (thrust):

等效汽油机: 10HP / 12HP

Peak Thrust in Lbs: 峰值推力:

250Lbs / 300Lbs Max Voltage: 电压:

DC 48V (AII)

Power - Max: 功率: 4320W / 6000W

Amp - Max: 电流:

90A / 125A

Depth Adjustment: 深度调节:

Not applicable (All)

Prop Type: 螺旋桨型号:

3blade prop / 11.8inch diam (All)

Prop Speed at Full Power: 转速: Max. 1050 rpm underwater (50733)

Max. 1200 rpm underwater (50734) **Battery Type Required:** 电池要求:

4x120AH Deep Cycle (50733) 4x250AH Deep Cycle (50734)

Steering: 转向操控: 360 degree control (All)

Decibel Level (db): 噪音等级:

75db (All)

Weight (N.W.): 重量:

27.3kg / 28.8kg

Shaft Type: 主杆类型: Cast Aluminium (All)

Shaft Length: 主杆长度:

540/670mm (All) **Colour:** 颜色: Black (All)

Max Boat Length (Suggestion): 船长:

9m (All)



STEPLESS SPEED CONTROLLER 无级变速器及感应开关

Digitally controlled step-less forward and reverse speed. Magnetic kill switch is included.



MOTOR TILING 角度调节支架

Offers 4 levels of tilting position with 3 angles additional option.



STEERING WHEEL CONTROL 另购方向盘操控

An additional steering wheel unit is required.
The steering angle: from -45° to +45°.



BATTERY METER LED电源电压显示

Shows voltage of battery all the time.



WATER COOLED 循环式水冷系统

Water cooling system operates when moving forward.

The Armada F series are equipped with dfficient 48V brushless motors providing powerful propulsion for a wide range of boats operating in various waterways. They offer flexible step-less speed adjustment and a safety lanyard offer an added degree of safety. These motors can easily be tilted in and out of the water so you can motor in almost any water level. The Armada F models also features a digital LED battery level indicator. An additional steering wheel unit is required. Suitable for both salt and fresh water use.

All Propellers Here





MODEL:24000225 3-blade prop. / 9.3 inch Suitable for MODEL:

50700, 50703, 50706, 50716, 50717, 50736



MODEL:24001176 3-blade prop. / 10.7 inch Suitable for MODEL:

50719, 50749, 50752, 50754, 50756



MODEL:24000236 2-blade prop. / 9 inch Suitable for MODEL: 50701, 50702, 50708, 50714

MODEL:24000522 2-blade prop. / 5.9 inch Suitable for MODEL: 50735



MODEL:24001273 3-blade prop. / 9.3 inch Suitable for MODEL:

50711, 50712, 50715, 50741, 50744, 50745



MODEL:24000333 3-blade prop. / 11.8 inch

Suitable for MODEL:

50713



MODEL:24001357 3-blade prop. / 11.8 inch Suitable for MODEL: 50731, 50732, 50733, 50734



MODEL:24000318 3-blade prop. / 11.8 inch

Suitable for MODEL:

50728



MODEL:24000825 2-blade prop. / 11.4 inch Suitable for MODEL:

50718D, 50737, 50738, 50739, 50757



MODEL:24002005 2-blade prop. / 7.6 inch Suitable for MODEL:

50765, 54706

Full Range Supply















紧急停止开关





Sacrificial Anode A

Sacrificial Anode B

牺牲阳极 B







Full Range Supply





无线脚踏控制器





MODEL:50805

2.4GHz; LCD Display; With USB Charger; 3.7V/1100mAh LIPO battery included.

Suitable for MODEL: 50736, 50737, 50739

Wired Foot Controller

有线脚踏控制器



MODEL:24000392 LCD Display

无线脚踏控制器

Suitable for MODEL:

50700, 50706, 50718D, 50757,

Wireless Foot Controller

Circuit Breaker 80A (Waterproof)

Circuit Breaker 200A 船用大电流开关(200A)

MODEL:59920

50734



Suitable for MODEL:50731, 50732, 50733,

50737,50738,50739

Wireless Remote Controller for GPS motors 无线遥控器(GPS)





MODEL:50806

2.4GHz: Bluetooth: Wifi: 3.7V/1100mAh LIPO battery included; With USB Charger

Suitable for MODEL: 50736, 50737, 50739



3.7V/1100mAh LIPO battery included.

Wireless Remote Controller for GPS motors

USB Charger

Suitable for MODEL:50738

Wireless Remote Controller 无线遥控器





MODEL:50802

433MHz; With USB Charger; 3.7V/200mAh LIPO battery included:

Suitable for MODEL: 50700, 50718D, 50706, 50757



MODEL:50809

无线遥控器(GPS)

2.4GHz; Bluetooth; Wifi; 3.7V/1100mAh LIPO battery included; With USB Charger

Suitable for MODEL:

50738



Battery Pack 29.6V/30Ah 锂电池



MODEL:59925

Suitable for MODEL:50741